



Lampu Emergency LED Outdoor 1\*T5 White Tube, andal & dapat diandalkan, tahan kondisi hujan (percikan air) & debu, baterai Ni-CD cell terbaik



## Description

**Lampu Emergency LED Outdoor 1\*T5 White Tube**, andal & dapat diandalkan, tahan kondisi hujan (percikan air) & debu, baterai Ni-CD cell terbaik.

Lihat produk serupa lainnya: [Lampu Emergency Anti Ledak LED 2x5w](#).

Spesifikasi produk lampu emergency LED outdoor 1\*T5 white tube ini sebagai berikut:

1. INPUT VOLTAGE : 230Vac 50/60Hz  $\pm$  10% A: 0.34 PF: 0.77
2. BATTERY : 2.4V 2.5AH/4.5AH High temp rated Nickel Cadmium cells or others
3. LAMP USED :
4. RATED PERIOD : > 2 hrs, 4 hrs & others
5. MODE : Non-maintained
6. OPERATION TEMPERATURE : ta 40 °C
7. CHARGE MONITOR : Super bright Green LED 5mm  $\varnothing$
8. RECHARGE PERIOD : 16 ~ 24 hrs
9. EMERGENCY LUMINANCE : > 8 cd/m<sup>2</sup>
10. ELECTROMAGNETIC FIELD : 17m gause @ 0.1m
11. CHARGER : Hybrid controlled charger
12. PROTECTION : Low volt cut-off to prevent battery over discharge Incoming AC fuse and Battery DC fuse Tropical climate protection coating on hybrid control circuit
13. CONSTRUCTION : Moulded Fire Retardant ABS base PC diffuser
14. DIMENSION : 340mm(L) x 120mm(W) x 70mm(H)
15. WEIGHT : 1.40kg (Net) / 1.60kg (Gross)
16. PACKING : One unit per carton
17. CARTON / DIMENSION : Double wall corrugated / 360mm(L) x 130mm(W) x 85mm(H)
18. COMPLIANCE : CP 19:2000, SS263: Part 2: 1998, IEC 598-2-22, AS 2293, SS 364